




Flat Top Cripmed Weave Wire Mesh Specification

When Odering, Please Specify:

1. Weave Type
2. Wire Diameter
3. Hole Size (L)
4. Roll Width (RW)
5. Roll Length (RL)
6. Material



Flat Top Cripmed Weave

Technical Parameter

		Opening L		Wire D		Open Area	Square Meter Weight (kgs)				
		mm	inch	mm	inch	%	Carbon Steel	Stainless Steel	Copper	Aluminum	Nickel
8.00 mm	4.00 mm	4.00	0.157	1.60	0.063	51.02	5.64	5.69	6.41	1.94	6.39
	6.00 mm	6.00	0.236	2.00	0.079	56.25	6.17	6.23	7.01	2.12	6.99
10.00 mm	8.00 mm	8.00	0.315	2.00	0.079	64.00	4.93	4.98	5.60	1.70	5.59
	10.00 mm	10.00	0.394	2.00	0.079	69.44	4.11	4.15	4.67	1.41	4.66
12.00 mm	10.00 mm	10.00	0.394	1.60	0.063	74.32	2.72	2.75	3.09	0.94	3.09
	12.00 mm	12.00	0.472	5.00	0.197	49.83	18.13	18.32	20.60	-	-
	12.00 mm	12.00	0.472	3.00	0.118	64.00	7.40	7.47	8.41	2.54	-
15.00 mm	12.00 mm	12.00	0.472	2.00	0.079	73.47	3.52	3.56	4.00	1.21	3.99
	15.00 mm	15.00	0.591	2.50	0.098	73.47	4.40	4.45	5.00	1.51	-
16.00 mm	15.00 mm	15.00	0.591	2.00	0.079	77.85	2.90	2.93	3.30	1.00	3.29
	16.00 mm	16.00	0.630	4.00	0.157	64.00	9.86	1.78	11.21	3.39	-
20.00 mm	16.00 mm	16.00	0.315	3.00	0.118	70.91	4.93	5.90	6.64	2.01	-
	20.00 mm	20.00	0.787	3.00	0.118	75.61	4.82	4.87	5.48	1.66	-
	20.00 mm	20.00	0.787	2.50	0.098	79.01	3.43	3.46	3.89	1.18	-
25.00 mm	20.00 mm	20.00	0.787	2.00	0.079	82.64	2.24	2.26	2.55	0.77	2.54
	25.00 mm	25.00	0.984	4.00	0.157	74.32	6.80	6.87	7.73	2.34	-
30.00 mm	25.00 mm	25.00	0.984	3.00	0.118	79.72	3.96	4.00	4.50	1.36	-
	30.00 mm	30.00	1.181	3.00	0.118	82.64	3.36	3.40	3.82	1.16	-
	40.00 mm	40.00	1.575	5.00	0.197	79.01	6.85	6.92	4.67	-	-
40.00 mm	40.00 mm	40.00	1.575	4.00	0.157	82.64	4.48	4.53	3.85	1.54	-
	40.00 mm	40.00	1.575	3.00	0.118	86.53	2.58	2.61	3.09	0.89	-
	50.00 mm	50.00	1.969	5.00	0.197	82.64	5.60	5.66	2.41	-	-
50.00 mm	50.00 mm	50.00	1.969	4.00	0.157	85.73	3.65	3.69	1.80	1.26	-
	50.00 mm	50.00	1.969	3.00	0.118	89.00	2.09	2.12	1.27	0.72	-
60.00 mm	60.00 mm	60.00	2.362	5.00	0.197	85.21	4.74	4.79	13.42	-	-