




H-Type Cable and Rod Combination Mesh Specification

When ordering, please specify:

1. Weave Type
2. Wire Diameter (D1 x D2)
3. Hole Size (P1 x P2)
4. Roll Width (RW)
5. Roll Length (RL)



H-Type Cable and Rod Combination Mesh

Technical Parameter

	Items	Cables		Rods		Open Area		Weight Kgs/m ²	
		Nos. x D1 (mm)	P1 (mm)	D2 (mm)	P2 (mm)	mm	%	Stainless Steel	Copper
110/10	HCR 110/10	3 x 3.0	110.0	4.0	14.5	100.0 x 10.5	66	8.60	9.72
100/5	HCR 100/5	3 x 4.0	112.0	4.0	8.0	100.0 x 4.0	46	13.60	15.37
80/20	HCR 80/20	3 x 2.0	80.0	3.0	20.0	74.0 x 17.0	78	5.40	6.10
80/10	HCR 80/10	3 x 2.0	80.0	3.0	10.0	74.0 x 7.0	62	6.65	7.51
	HCR 80/10	3 x 2.2	80.0	3.0	10.0	73.6 x 7.0	64	7.00	7.91
	HCR 80/10	3 x 1.6	80.0	2.5	10.0	75.2 x 7.5	70	4.58	5.18
75/10	HCR 70/5	4 x 1.0	72.0	2.0	7.0	68.0 x 5.0	67	3.98	4.50
12/3	HCR 42/3	4 x 2.0	50.0	3.0	6.0	42.0 x 3.0	42	11.2	12.66
35/10	HCR 35/10	2 x 2.75	40.0	4.0	14.5	34.5 x 10.5	62	9.40	10.62
32/5	HCR 32/5	4 x 1.0	36.0	2.0	6.6	32.0 x 4.6	62	4.55	5.14
32/2	HCR 32/2	4 x 1.0	36.0	2.0	4.0	32.0 x 2.0	44	6.89	7.78
	HCR 32/2	4 x 0.75	35.0	1.6	3.5	32.0 x 2.0	50	4.80	5.42
23/2	HCR 23/2	4 x 0.75	26.4	1.5	3.0	23.4 x 1.5	44	5.20	5.88
	HCR 23/2	4 x 0.75	24.5	1.5	3.5	21.5 x 2.0	50	4.30	4.86
8/8	HCR 8/8	2 x 2.75	13.5	2.0	10	8.0 x 8.0	47	7.65	8.64
6/6	HCR 6/6	1 X 1.75	7.5	2.5	8.2	5.75 x 5.7	53	6.85	7.74
4/6	HCR 4/6	1 X 2.6	6.8	2.0	7.5	4.2 x 5.5	45	6.60	7.46
	HCR 4/6	1 x 2.5	6.0	2.0	8.0	3.5 x 6.0	43	7.87	8.89
4/4	HCR 4/4	1 x 2.4	6.0	2.0	6.0	3.6 x 4.0	40	8.90	10.06
4/3	HCR 4/3	1 x 2.4	6.0	3.0	6.0	3.6 x 3.0	30	14.60	16.50
2/7	HCR 2/7	1 x 3.0	5.0	3.0	10.0	2.0 x 7.0	28	14.80	16.72
2/4	HCR 2/4	1 x 1.8	4.0	1.5	5.5	2.2 x 4.0	40	7.74	8.75
2/1	HCR 2/1	3 X 0.45	3.5	0.5	1.6	2.25 x 1.1	43	2.10	2.37
1/4	HCR 1/3	1 x 1.8	3.0	2.0	5.0	1.2 x 3.0	24	9.97	11.27