




H-Type Pre-crimp Wire and Rod Combination Mesh Specification

When ordering, please specify:

1. Weave Type
2. Wire Diameter (D1 x D2)
3. Hole Size (P1 x P2)
4. Roll Width (RW)
5. Roll Length (RL)



H-Type Pre-crimp Wire and Rod Combination Mesh

Technical Parameter

	Items	Pre-crimp Wire		Rods		Open Area		Weight Kgs/m2	
		Nos. x D1 (mm)	P1 (mm)	D2 (mm)	P2 (mm)	mm	%	Stainless Steel	Copper
120/10	HPR 120/10	3 X 2.75	125.0	4.0	14.5	116.75 x 10.5	64	8.26	9.33
100/10	HPR 100/10	3 x 3.0	110.0	4.0	14.0	100.0 x 10.0	65	9.32	10.53
	HPR 100/5	3 x 2.0	100.0	3.0	8.0	94.0 x 5.0	59	8.36	9.45
80/10	HPR 80/10	3 x 2.0	86.0	3.0	12.0	80.0 x 9.0	65	8.61	9.73
80/7	HPR 80/7	1 x 2.0	80.0	2.0	7.0	78.0 x 5.0	70	4.10	4.63
	HPR 80/7	3 x 2.0	80.0	3.0	7.0	74.0 x 3.75	55	9.30	10.51
80/5	HPR 80/5	3 x 2.0	80.0	2.5	5.25	74.0 x 3.75	55	8.50	9.61
70/8	HPR 70/8	3 x 2.5	77.5	3.0	11.0	70.0 x 8.0	64	8.00	9.04
70/4	HPR 70/4	3 x 2.0	76.0	2.0	5.5	70.0 x 3.5	56	7.50	8.48
67/17	HPR 67/17	3 x 2.5	75.0	3.0	20.0	67.5 x 17.0	77	5.50	6.22
67/11	HPR 67/11	3 x 2.5	75.0	3.0	14.0	67.5 x 11.0	71	6.00	6.78
67/7	HPR 67/7	3 x 2.5	75.0	3.0	10.0	67.5 x 7.4	64	7.40	8.36
42/3	HPR 42/3	4 x 2.0	50.0	3.0	6.0	42.0 x 3.0	42	11.97	13.53
35/4	HPR 35/4	3 x 1.0	38.0	4.0	8.0	35.0 x 4.0	45	12.82	14.49
31/2	HPR 31/2	3 x 1.25	35.0	2.0	4.0	31.0 x 2.0	43	7.38	8.34
	HPR 31/2	4 x 0.75	34.0	1.5	3.5	31.0 x 2.0	53	4.30	4.86
23/2	HPR 23/2	4X 0.75	26.4	1.5	3.0	23.4 x 1.5	44	5.20	5.88
	HPR 23/2	3 x 1.0	26.4	1.6	3.2	23.4 x 1.6	44	5.80	6.55