





Intermediate Crimped Weave Wire Mesh Specification

When Ordering, Please Specify:

1. Weave Type
2. Wire Diameter
3. Hole Size (L)
4. Roll Width (RW)
5. Roll Length (RL)
6. Material



Single Inter Crimp Weave



Double Inter Crimp Weave

Technical Parameter

	Opening L		Wire D		Open Area %	Square Meter Weight (kgs)				
	mm	inch	mm	inch		Carbon Steel	Stainless Steel	Copper	Aluminum	Nickel
5.00 mm	5.00	0.197	1.00	0.039	69.44	2.06	2.08	2.34	0.71	2.33
	5.00	0.197	0.90	0.035	71.82	1.69	1.71	1.92	-	1.92
	5.00	0.197	0.80	0.031	74.32	1.36	1.37	1.55	-	1.54
	5.00	0.197	0.70	0.028	76.95	1.06	1.07	1.20	-	1.20
	5.00	0.197	0.60	0.024	79.72	0.79	0.80	0.90	-	0.90
6.00 mm	6.00	0.236	1.00	0.039	73.47	1.76	1.78	2.00	0.61	2.00
	6.00	0.236	0.80	0.031	77.85	1.16	1.17	1.32	-	1.32
	6.00	0.236	0.60	0.024	82.64	0.67	0.68	0.76	-	0.76
7.00 mm	7.00	0.276	1.40	0.055	69.44	2.88	2.91	3.27	0.99	3.26
	7.00	0.276	1.20	0.047	72.87	2.17	2.19	2.46	0.74	2.45
	7.00	0.276	1.00	0.039	76.56	1.54	1.56	1.75	0.53	1.75
	7.00	0.276	0.80	0.031	80.54	1.01	1.02	1.15	-	1.15
8.00 mm	8.00	0.315	4.00	0.157	44.44	16.44	16.61	18.68	5.65	-
	8.00	0.315	1.60	0.063	69.44	3.29	3.32	3.74	1.13	3.73
	8.00	0.315	1.40	0.055	72.43	2.57	2.60	2.92	0.88	2.91
	8.00	0.315	1.20	0.047	75.61	1.93	1.95	2.19	0.66	2.19
	8.00	0.315	1.00	0.039	79.01	1.37	1.38	1.56	0.47	1.55
	8.00	0.315	0.80	0.031	82.64	0.90	0.91	1.02	-	1.02
10.00 mm	10.00	0.394	2.00	0.079	69.44	4.11	4.15	4.67	1.41	4.66
	10.00	0.394	1.80	0.071	71.82	3.39	3.42	3.85	1.16	3.84
	10.00	0.394	1.60	0.063	74.32	2.72	2.75	3.09	0.94	3.09
	10.00	0.394	1.40	0.055	76.95	2.12	2.14	2.41	0.73	2.40
	10.00	0.394	1.20	0.047	79.72	1.59	1.60	1.80	0.55	1.80
	10.00	0.394	1.00	0.039	82.64	1.12	1.13	1.27	0.39	1.27
12.70 mm	12.70	0.500	2.60	0.102	68.90	5.45	5.50	6.19	1.87	-
	12.70	0.500	2.30	0.091	71.68	4.35	4.39	4.94	1.50	-
	12.70	0.500	2.00	0.079	74.64	3.36	3.39	3.81	1.15	3.80
	12.70	0.500	1.80	0.071	76.71	2.76	2.78	3.13	0.95	3.12
	12.70	0.500	1.60	0.063	78.87	2.21	2.23	2.51	0.76	2.50
	12.70	0.500	1.40	0.055	81.13	1.71	1.73	1.95	0.59	1.94
	12.70	0.500	1.20	0.047	83.48	1.28	1.29	1.45	0.44	1.45
20.00 mm	20.00	0.787	4.00	0.157	69.44	8.22	8.30	9.34	2.83	-
	20.00	0.787	3.60	0.142	71.82	6.77	6.84	7.69	2.33	-

	Opening L		Wire D		Open Area	Square Meter Weight (kgs)				
	mm	inch	mm	inch	%	Carbon Steel	Stainless Steel	Copper	Aluminum	Nickel
20.00 mm	20.00	0.787	3.20	0.126	74.32	5.44	5.50	6.18	1.87	-
	20.00	0.787	2.90	0.114	76.28	4.53	4.57	5.15	1.56	-
	20.00	0.787	2.60	0.102	78.31	3.69	3.73	4.19	1.27	-
	20.00	0.787	2.30	0.091	80.44	2.93	2.95	3.32	1.01	-
	20.00	0.787	2.00	0.079	82.64	2.24	2.26	2.55	0.77	2.54
	20.00	0.787	1.80	0.071	84.17	1.83	1.85	2.08	0.63	2.08
25.40 mm	25.40	1.000	4.80	0.189	70.74	9.41	9.50	10.69	-	-
	25.40	1.000	4.40	0.173	72.65	8.01	8.09	9.10	-	-
	25.40	1.000	4.00	0.157	74.64	6.71	6.78	7.63	2.31	-
	25.40	1.000	3.60	0.142	76.71	5.51	5.57	6.26	1.90	-
	25.40	1.000	3.20	0.126	78.87	4.41	4.46	5.02	1.52	-
	25.40	1.000	2.90	0.114	80.56	3.66	3.70	4.16	1.26	-
	25.40	1.000	2.60	0.102	82.29	2.98	3.01	3.38	1.02	-
	25.40	1.000	2.30	0.091	84.08	2.35	2.38	2.68	0.81	-
	25.40	1.000	2.00	0.079	85.93	1.80	1.82	2.05	0.62	2.04
38.10 mm	38.10	1.500	5.80	0.228	75.32	9.45	9.54	10.74	-	-
	38.10	1.500	5.30	0.209	77.07	7.98	8.06	9.07	-	-
	38.10	1.500	4.80	0.189	78.87	6.62	6.69	7.52	-	-
	38.10	1.500	4.40	0.173	80.37	5.62	5.67	6.38	-	-
	38.10	1.500	4.00	0.157	81.90	4.69	4.73	5.32	1.61	-
	38.10	1.500	3.60	0.142	83.48	3.83	3.87	4.35	1.32	-
	38.10	1.500	3.20	0.126	85.10	3.06	3.09	3.47	1.05	-
	38.10	1.500	2.90	0.114	86.35	2.53	2.56	2.87	0.87	-
	38.10	1.500	2.60	0.102	87.63	2.05	2.07	2.33	0.70	-
50.80 mm	50.80	2.000	5.80	0.228	80.56	7.33	7.40	8.33	-	-
	50.80	2.000	5.30	0.209	82.00	6.17	6.24	7.02	-	-
	50.80	2.000	4.80	0.189	83.48	5.11	5.16	5.81	-	-
	50.80	2.000	4.40	0.173	84.69	4.32	4.37	4.91	-	-
	50.80	2.000	4.00	0.157	85.93	3.60	3.64	4.09	1.24	-
	50.80	2.000	3.60	0.142	87.20	2.94	2.97	3.34	1.01	-
	50.80	2.000	3.20	0.126	88.50	2.34	2.36	2.66	0.8	-
	50.80	2.000	2.90	0.114	89.49	1.93	1.95	2.19	0.66	-
63.50 mm	63.50	2.500	5.80	0.228	83.96	5.99	6.05	6.80	-	-
	63.50	2.500	5.30	0.209	85.19	5.03	5.09	5.72	-	-
	63.50	2.500	4.80	0.189	86.44	4.16	4.20	4.73	-	-
	63.50	2.500	4.40	0.173	87.46	3.52	3.55	3.99	-	-
	63.50	2.500	4.00	0.157	88.50	2.92	2.95	3.32	1.01	-
76.20 mm	76.20	3.000	5.80	0.228	86.35	5.06	5.11	5.75	-	-
	76.20	3.000	5.30	0.209	87.42	4.25	4.29	4.83	-	-
	76.20	3.000	4.80	0.189	88.50	3.51	3.54	3.99	-	-
88.90 mm	88.90	3.500	5.80	0.228	88.13	4.38	4.42	4.98	-	-
	88.90	3.500	5.30	0.209	89.06	3.68	3.71	4.18	-	-
101.06 mm	101.60	4.000	5.80	0.228	89.49	3.86	3.90	4.39	-	-
	101.60	4.000	5.30	0.209	90.33	3.24	3.27	3.68	-	-